
Appliance Clamp tiltable 2T413G-2H (23.11.2026)



with independent sideshift - rubber coated arms - both arms 90° forward tipping - 2 hydraulic functions + solenoid valve

Model	Cap. kg	LCD mm	S mm	A mm	B mm	F mm	E mm	G mm	J mm	ISO	V mm	CofG Z mm	CofG$_V$ Y mm	Weight kg	Price 人民币
2T413G-2H	300	1.000	±100	540-2.160	1.260	1.200	102	580	1.000	2	143	670	265	790	On request
2T413G-2H	300	1.000	±100	540-2.160	1.260	1.200	102	580	1.000	3	143	670	265	790	On request

Add-on price for 100mm armlength / -height on request,
For contact pad coatings see accessories in the pricelist.
Also available without sideshift, model 2T403G-2H
Load Backrest see model T179.

Appliance Clamp tiltable 2T413G-2H

Specification:

With the KAUP Appliance Clamp tiltable

2T413G-2H it is possible to take up loading property and to set down 90°

recumbent safely. Therefore, this attachment is suited especially to

move stored goods or to load and unload truck, carriages and containers

and to use, besides, the height optimally.

Qualities:

- Independent sideshift serially
- Contact pads of the clamp arms up to 90° hydraulically tiltably
- Load backrest optionally