



with independent sideshift - rubber coated arms - both arms 90° forward tipping - 2 hydraulic functions + solenoid valve

Technical Data

| Model | Cap. kg | LCD mm | S mm | A mm | B mm | F mm | E mm | G mm | J mm | ISO | V mm | CofG Z mm | CofG _v Y mm | Weight kg | Price 人民币 |
|-----------|------------|-----------|---------|-----------|---------|---------|---------|---------|---------|-----|---------|-----------------|------------------------------|--------------|--------------|
| 2T413G-2H | 300 | 1.000 | ±100 | 540-2.160 | 1.260 | 1.200 | 102 | 580 | 1.000 | 2 | 143 | 670 | 265 | 790 | On request |
| 2T413G-2H | 300 | 1.000 | ±100 | 540-2.160 | 1.260 | 1.200 | 102 | 580 | 1.000 | 3 | 143 | 670 | 265 | 790 | On request |

Add-on price for 100mm armlength / -height on request,
For contact pad coatings see accessories in the pricelist.
Also available without sideshift, model 2T403G-2H
Load Backrest see model T179.



Appliance Clamp tiltable 2T413G-2H

Specification:

With the KAUP Appliance Clamp tiltable

2T413G-2H it is possible to take up loading property and to set down 90°

recumbent safely. Therefore, this attachment is suited especially to

move stored goods or to load and unload truck, carriages and containers

and to use, besides, the height optimally.

Qualities:

- Independent sideshift serially
- Contact pads of the clamp arms up to 90° hydraulically tiltable
- Load backrest optionally