



to enlarge the width of the original fork carriage or as false carriage for fork drop-off

## Technical Data

| Model | Cap.<br>kg | LCD<br>mm | B<br>mm | ISO | V<br>mm | CofG<br>Z<br>mm | CofG <sub>v</sub><br>Y<br>mm | Weight<br>kg | Price<br>人民币 |
|-------|------------|-----------|---------|-----|---------|-----------------|------------------------------|--------------|--------------|
| 2T013 | 2.500      | 600       | 920     | 2   | 65      | 38              | 206                          | 68           | On request   |
| 2T013 | 2.500      | 600       | 980     | 2   | 65      | 39              | 206                          | 70           | On request   |
| 2T013 | 2.500      | 600       | 1.020   | 2   | 65      | 39              | 206                          | 72           | On request   |
| 2T013 | 2.500      | 600       | 1.040   | 2   | 65      | 39              | 206                          | 73           | On request   |
| 2T013 | 2.500      | 600       | 1.150   | 2   | 65      | 41              | 205                          | 93           | On request   |
| 2T013 | 2.500      | 600       | 1.600   | 2   | 75      | 49              | 203                          | 143          | On request   |

|       |       |     |       |   |    |    |     |     |            |
|-------|-------|-----|-------|---|----|----|-----|-----|------------|
| 3T013 | 3.000 | 500 | 1.020 | 3 | 75 | 46 | 256 | 101 | On request |
| 3T013 | 3.000 | 500 | 1.070 | 3 | 75 | 46 | 256 | 105 | On request |
| 3T013 | 3.000 | 500 | 1.100 | 3 | 75 | 46 | 256 | 107 | On request |
| 3T013 | 3.000 | 500 | 1.150 | 3 | 75 | 47 | 256 | 110 | On request |
| 3T013 | 3.000 | 500 | 1.300 | 3 | 75 | 48 | 255 | 127 | On request |
| 3T013 | 3.000 | 500 | 1.600 | 3 | 85 | 55 | 254 | 203 | On request |

|         |       |     |       |   |    |    |     |     |            |
|---------|-------|-----|-------|---|----|----|-----|-----|------------|
| 4,8T013 | 5.000 | 600 | 1.150 | 3 | 75 | 42 | 278 | 128 | On request |
| 4,8T013 | 5.000 | 600 | 1.200 | 3 | 75 | 42 | 277 | 132 | On request |
| 4,8T013 | 5.000 | 600 | 1.300 | 3 | 75 | 43 | 275 | 145 | On request |
| 4,8T013 | 5.000 | 600 | 1.310 | 3 | 75 | 43 | 275 | 145 | On request |
| 4,8T013 | 5.000 | 600 | 1.350 | 3 | 75 | 44 | 274 | 148 | On request |
| 4,8T013 | 5.000 | 600 | 1.410 | 3 | 75 | 44 | 274 | 152 | On request |
| 4,8T013 | 5.000 | 600 | 1.600 | 3 | 85 | 51 | 267 | 220 | On request |
| 4,8T013 | 5.000 | 600 | 1.800 | 3 | 85 | 52 | 266 | 237 | On request |
| 4,8T013 | 5.000 | 600 | 2.000 | 3 | 85 | 53 | 265 | 255 | On request |

|       |       |     |       |   |     |    |     |     |            |
|-------|-------|-----|-------|---|-----|----|-----|-----|------------|
| 8T013 | 8.000 | 600 | 1.400 | 4 | 90  | 51 | 352 | 246 | On request |
| 8T013 | 8.000 | 600 | 1.800 | 4 | 100 | 60 | 345 | 348 | On request |
| 8T013 | 8.000 | 600 | 2.180 | 4 | 100 | 61 | 342 | 397 | On request |
| 8T013 | 8.000 | 600 | 2.260 | 4 | 110 | 67 | 338 | 466 | On request |

Load Backrest see model T179.

Other construction widths available upon request.

Available in combination with quick release bottom hooks for quick change fork applications to other attachments.  
Fork Carriage with artificial lost load center distance available upon request.



### Specification:

The existing fork carriage of the

forklift truck can be extended with a KAUP Fork Carriage type T013. It

can also be used for quick change between attachments and/or forks.

Upon

request KAUP Fork Carriages can be supplied to increase the lost load

centre and as adapter fork carriage between the forklift truck and other

attachments.

## Qualities:

---

- Solid construction for heavy duty operation
- Best visibility