



1 hydraulic function

Technical Data

Model	A	B	C	P	R	T	Closing force at 120 bar N	ISO	V mm	CofG Z mm	CofG _v Y mm	CofG _v Y1 mm	Weight kg	Price 人民币
	mm	mm	mm	mm	mm	mm								
1T124ST	1.515	1.175-2.995	1.650	605	800	1.000	3.700	2	204	217	749	1.732	273	On request
1T124ST	1.515	1.175-2.995	1.650	605	800	1.000	3.700	3	204	217	749	1.732	273	On request
1T124.1ST	1.190	950-2.570	1.550	605	800	1.000	3.700	2	204	231	627	1.515	248	On request
1T124.1ST	1.190	950-2.570	1.550	605	800	1.000	3.700	3	204	231	627	1.515	248	On request
1T124.2ST	940	750-1.930	1.160	605	800	1.000	3.700	2	204	253	522	1.190	216	On request
1T124.2ST	940	750-1.930	1.160	605	800	1.000	3.700	3	204	253	522	1.190	216	On request

The total height is the result of adding fig. A + C.

To choose the right fork length please consider dimension „V“.

The standard contact pad frame is alternatively available in 770 x 920 mm or 800 x 1.000 mm.

Increased contact pad on request.



Specification:

The KAUP Telescopic Load Stabilizer

T124ST has a large opening range with a low construction height.

Therefore this Load Stabilizer is best suited for large volume goods, e.g. for stabilizing and securing stacks of Euro pallets.

Qualities:

- Solid construction
- Good visibility conditions
- Combination with other attachments possible