


Reach Fork T140SV (24.10.2025)



with independent sideshift - 2 hydraulic functions

Technical Data

Model	Cap. extended kg	Cap. retracted kg	LCD mm	S	B mm	C mm	D mm	D1 mm	E mm	G mm	H mm	ISO	V	CofG Z mm	CofG Z1 mm	Weight kg	Price 人民币
2T140SV	2.000	2.500	600	±100	800	950	70	50	140	1.200	800	2	310	373	685	430	On request
2T140SV	2.000	2.500	600	±100	800	950	70	50	140	1.200	800	3	310	332	607	490	On request

Max. distance from fork tip to mast = G + V + C + thickness of FLT carriage.

Also available without sideshift, model T140

Without sideshift the lost load center is reduced by approx. 30 mm

KAUP

Reach Fork T140SV



KAUP Reach Forks T140SV combine the

Specification:

advantages of reach trucks - narrow working aisles with the lost load centre close to the front chassis - with those of the counterbalance forklift truck. The mobile fork on the backrest - the Reach Fork - inserts under the pallet. At the same time the fixed bearing forks support the loading process. By retracting the Reach Forks and backrest

the load is moved to the bearing area of the forklift truck. It can then

Qualities:

Very good residual capacity

be picked up and transported.

- · Good visibility conditions
- Solid design
- Sideshift serially