



2 hydraulic functions - and built-in solenoid valve with accessory kit

Technical Data

Model	Cap. kg	LCD mm	B mm	C mm	D mm	E mm	F mm	S mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
1T146S	1.000	600	1.000	1.300	1.035	20	1.250	±100	2	268	320	585	On request
2T146S	1.700	600	1.000	1.300	1.035	25	1.250	±100	2	273	335	645	On request
2T146S	1.700	600	1.000	1.300	1.035	25	1.250	±100	3	273	335	645	On request
3T146S	2.400	600	1.000	1.300	1.035	30	1.250	±100	3	278	345	710	On request

Lifting heights of more than 3.750 mm require an electric spring cable drum. See accessories in the pricelist.



Specification:

Mounted directly on to the fork carriage

the KAUP Push-Pull with sideshift and sheet saver T146S is the right choice when slip-sheets are regularly used as transport mode. In order to separate the complete load from the slip-sheet during pushing, the attachment is fitted with a so called pallet retainer. It grips the slip-sheet firmly while the load is pushed off so that the slip-sheet can be used several times. Serially fitted sideshift ensures simple and exact positioning of the attachment.

Like all other KAUP Push-Pulls, this range also has a large surfaced carrying plate for transportation of palletless loads.

Qualities:

- Solid construction
- Good visibility conditions through the attachment
- Good residual capacity
- Self supporting scissor system
- Sideshift serially