Sideshifter High-Performance Model T151P2

(24.11.2026)



1 hydraulic function, Quick mounting, hook-on type, end-of-stroke slow-down SOFTSTOP, high visibility design, e.g. CofG up to 1.800 mm, Bottom brackets with roller guidance, SMOOTHROLL.

Model	Cap. kg	LCD mm	A mm	B mm	C mm	D mm	S mm	G mm	J mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
2T151P2	2.500	600	76	890	44	32	±100	116	858	2	72	37	70	On request
2T151P2	2.500	600	76	920	44	32	±100	116	858	2	72	37	72	On request
2T151P2	2.500	600	76	980	44	32	±100	116	858	2	72	38	74	On request
2T151P2	2.500	600	76	1.020	44	32	±100	116	858	2	72	39	76	On request
2T151P2	2.500	600	76	1.040	44	32	±100	116	858	2	72	39	77	On request
2T151P2	2.500	600	76	1.150	44	32	±100	116	858	2	72	43	97	On request
2T151P2	2.500	600	76	1.600	54	32	±100	116	858	2	82	52	146	On request
3T151P2[1)]	3.000	500	76	1.020	54	34	±100	116	858	3	82	45	106	On request
3T151P2[1)]	3.000	500	76	1.070	54	34	±100	116	858	3	82	45	110	On request
3T151P2[1)]	3.000	500	76	1.100	54	34	±100	116	858	3	82	46	112	On request
3T151P2[1)]	3.000	500	76	1.150	54	34	±100	116	858	3	82	46	115	On request
3T151P2[1)]	3.000	500	76	1.300	54	34	±100	116	858	3	82	48	132	On request
3T151P2[1)]	3.000	500	76	1.600	64	34	±100	116	858	3	92	57	207	On request
4T151P2	5.000	500	85	1.100	50	40	±100	125	1.040	3	82	41	136	On request
4T151P2	5.000	500	85	1.150	50	40	±100	125	1.040	3	82	41	139	On request
4T151P2	5.000	500	85	1.200	50	40	±100	125	1.040	3	82	42	143	On request
4T151P2	5.000	500	85	1.300	50	40	±100	125	1.040	3	82	44	156	On request
4T151P2	5.000	500	85	1.350	50	40	±100	125	1.040	3	82	44	165	On request
4T151P2	5.000	500	85	1.600	60	40	±100	125	1.040	3	92	54	231	On request
4T151P2	5.000	500	85	1.800	60	40	±100	125	1.040	3	92	55	248	On request
4T151P2	5.000	500	85	2.000	60	40	±100	125	1.040	3	92	56	256	On request
4,8T151P2	5.000	600	103	1.150	42	44	±100	165	922	3	82	39	149	On request
4,8T151P2	5.000	600	103	1.200	42	44	±100	165	922	3	82	40	153	On request
4,8T151P2	5.000	600	103	1.300	42	44	±100	165	922	3	82	42	166	On request
4,8T151P2	5.000	600	103	1.310	42	44	±100	165	922	3	82	42	166	On request
4,8T151P2	5.000	600	103	1.350	42	44	±100	165	922	3	82	42	175	On request
4,8T151P2	5.000	600	103	1.410	42	44	±100	165	922	3	82	44	190	On request
4,8T151P2	5.000	600	103	1.600	52	44	±100	165	922	3	92	52	241	On request

Model	Cap. kg	LCD mm	A mm	B mm	C mm	D mm	S mm	G mm	J mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
4,8T151P2	**5.000**	**600**	**103**	**1.800**	**52**	**44**	**±100**	**165**	**922**	**3**	**92**	**53**	**258**	**On request**
4,8T151P2	**5.000**	**600**	**103**	**2.000**	**52**	**44**	**±100**	**165**	**922**	**3**	**92**	**56**	**313**	**On request**
5T151P2	5.000	600	80	1.220	60	42	±100	125	1.040	4	92	51	212	On request
5T151P2	**5.000**	**600**	**80**	**1.400**	**60**	**42**	**±100**	**125**	**1.040**	**4**	**92**	**53**	**231**	**On request**
5T151P2	**5.000**	**600**	**80**	**1.800**	**70**	**42**	**±100**	**125**	**1.040**	**4**	**102**	**63**	**334**	**On request**
5T151P2	**5.000**	**600**	**80**	**2.180**	**70**	**42**	**±100**	**125**	**1.040**	**4**	**102**	**63**	**383**	**On request**
5T151P2	5.000	600	80	2.260	70	53	±100	125	1.040	4	112	65	455	On request
5,5T151P2	7.000	600	96	1.220	52	44	±100	156	922	4	92	50	230	On request
5,5T151P2	**7.000**	**600**	**96**	**1.400**	**52**	**44**	**±100**	**156**	**922**	**4**	**92**	**51**	**249**	**On request**
5,5T151P2	**7.000**	**600**	**96**	**1.800**	**62**	**44**	**±100**	**156**	**922**	**4**	**102**	**61**	**352**	**On request**
5,5T151P2	**7.000**	**600**	**96**	**2.180**	**62**	**44**	**±100**	**156**	**922**	**4**	**102**	**62**	**401**	**On request**
5,5T151P2	7.000	600	96	2.260	62	44	±100	156	922	4	102	62	473	On request
6T151P2	**8.000**	**600**	**112**	**1.400**	**50**	**53**	**±160**	**212**	**1.392**	**4**	**92**	**42**	**295**	**On request**
6T151P2	**8.000**	**600**	**112**	**1.800**	**60**	**53**	**±160**	**212**	**1.392**	**4**	**102**	**53**	**397**	**On request**
6T151P2	**8.000**	**600**	**112**	**2.180**	**60**	**53**	**±160**	**212**	**1.392**	**4**	**102**	**55**	**446**	**On request**
6T151P2	8.000	600	112	2.260	70	53	±160	212	1.392	4	112	61	516	On request
10T151	8.000	1.100	112	1.800	54	53	±160	45	1.510	4	106	46	455	On request
10T151	8.000	1.100	112	2.000	54	53	±160	45	1.510	4	106	46	490	On request
10T151	8.000	1.100	112	2.260	54	53	±160	45	1.510	4	106	46	535	On request
10T151	8.000	1.100	112	2.400	54	53	±160	45	1.510	4	106	46	560	On request

1) Exclusively for FLT’s with 3.000 kg. capacity at 500 mm LCD.
Load Backrest see model T179.
Additional for T151P2 (add-on price): Load backrest drill holes, set of adapter connection, hose kit and set of quick release system
Other construction widths available upon request.
Optional in explosion proof version

Sideshifter High-Performance Model T151P2





Specification:

Many requirements and different widths

of fork carriages require an unlimited number of variations. The KAUP

High-Performance Sideshifter type T151P2 supplies this variation. In

addition, all sideshifter components such as housings, pistons and

brackets are identical in design as those used in other KAUP attachments

with additional sideshift function. This optimises maintenance and

simplifies repairs.

Qualities:

- Strong design for heavy duty operation
- Best visibility
- Construction widths of up to 3.500 mm possible
- Equal shifting force and shifting speeds in both directions