



with valveblock sideshift dependent on the opening range - without forks - for forks acc. to ISO 2330 - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A mm	A1 mm	A2 mm	B mm	C mm	suitable for max. fork width mm	VSmax mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
2T160BI	2.500	500	150-850	250-950	320-1.020	1.040	240	120	±175	2	116	51	117	On request
2T160BI	2.500	500	150-950	250-1.050	320-1.120	1.150	240	120	±200	2	116	51	123	On request
2,5T160BI	2.500	600	150-850	250-950	320-1.020	1.040	240	120	±175	2	126	57	126	On request
2,5T160BI	2.500	600	150-950	250-1.050	320-1.120	1.150	240	120	±200	2	126	57	132	On request
3,5T160BI	3.600	500	180-980	250-1.050	320-1.120	1.150	240	130	±200	3	141	61	173	On request
3,5T160BI	3.600	500	180-1.180	250-1.250	320-1.320	1.350	240	130	±250	3	141	61	188	On request
4,8T160BI¹⁾	5.000	600	180-1.180	250-1.250	320-1.320	1.350	255	150	±250	3	141	63	250	On request
4,8T160BI¹⁾	5.000	600	180-1.360	250-1.430	320-1.500	1.550	255	150	±295	3	141	63	269	On request
6T160BI	6.000	600	260-1.170	350-1.260	440-1.350	1.460	330	150	±227,5	4	166	64	395	On request
6T160BI	6.000	600	260-1.360	350-1.450	440-1.540	1.650	330	150	±275	4	166	63	411	On request
6T160BI	6.000	600	260-1.560	350-1.650	440-1.740	1.860	330	150	±325	4	166	61	457	On request
8T160BI	8.000	600	260-1.560	350-1.650	440-1.740	1.860	330	150	±325	4	166	61	457	On request
8T160BI	8.000	600	260-1.760	350-1.850	440-1.940	2.060	330	150	±375	4	166	61	474	On request
8T160BI	8.000	600	260-1.960	350-2.050	440-2.140	2.260	330	150	±425	4	166	62	490	On request

Model	Cap. kg	LCD mm	A mm	A1 mm	A2 mm	B mm	C mm	suitable for max. fork width mm	VSmax mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
8T160BI	8.000	600	260- 2.060	350- 2.150	440- 2.240	2.400	330	150	±450	4	166	62	502	On request

10T160BI	8.000	1.100	260- 1.760	360- 1.860	460- 1.960	2.060	370	200	±375	4	210	97	605	On request
10T160BI	8.000	1.100	260- 1.960	360- 2.060	460- 2.160	2.260	370	200	±425	4	210	96	635	On request
10T160BI	8.000	1.100	260- 2.060	360- 2.160	460- 2.260	2.400	370	200	±450	4	210	94	654	On request

1) 4,8T with capacity (kg/mm) 2.700/1.200 available upon request.

CofG and weight measurements do not take the cheek plates into account.

Fork carriage drawings, roller studs and chain anchors to be supplied by customer if necessary.

Not suitable for clamping between the forks.

Available without sideshift.

Load backrest see model T479 and T479.1

Forks see model T180.

Higher capacities and other construction widths available upon request.



Specification:

The KAUP integrated Fork Positioner

T160BI is an economical integrated Fork Positioner with excellent view to the fork tips and load. Compared to hook-on attachments in the T160 range this Fork Positioner has an even better, higher residual capacity.

Qualities:

- Economical integrated Fork Positioner for moderately heavy operation
- Excellent residual capacity
- High stability with optimal tare weight
- Very good visibility conditions
- Valve block sideshift serially
- Original forklift trucks useable