



with valveblock sideshift dependent on the opening range - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	VSmax mm	ISO	V mm	CofG Z mm	CofG _v Y mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
1,5T160BZ	1.600	500	170-810	980	40	100	1.200	±160	2	71	245	134	209	On request	On request
1,5T160BZ	1.600	500	170-870	1.040	40	100	1.200	±175	2	71	240	135	213	On request	On request
1,5T160BZ	1.600	500	170-970	1.150	40	100	1.200	±200	2	71	234	137	219	On request	On request
2T160BZ	2.500	500	130-770	980	45	120	1.200	±160	2	71	284	118	244	On request	On request
2T160BZ	2.500	500	130-830	1.040	45	120	1.200	±175	2	71	280	120	247	On request	On request
2T160BZ	2.500	500	130-930	1.150	45	120	1.200	±200	2	71	273	122	253	On request	On request
2T160BZ	2.500	500	130-1.130	1.350	45	120	1.200	±250	2	71	263	125	265	On request	On request
2,5T160BZ	2.500	600	130-830	1.040	50	120	1.200	±175	2	71	274	126	266	On request	On request
2,5T160BZ	2.500	600	130-930	1.150	50	120	1.200	±200	2	71	269	128	272	On request	On request
3,5T160BZ	3.600	500	130-830	1.040	50	150	1.200	±175	3	71	308	126	302	On request	On request
3,5T160BZ	3.600	500	130-930	1.150	50	150	1.200	±200	3	71	303	129	307	On request	On request
3,5T160BZ	3.600	500	130-1.030	1.250	50	150	1.200	±225	3	71	300	131	312	On request	On request
3,5T160BZ	3.600	500	130-1.130	1.350	50	150	1.200	±250	3	71	292	133	317	On request	On request
3,5T160BZ	3.600	500	130-1.330	1.550	50	150	1.200	±300	3	71	292	138	327	On request	On request
3,5T160BZ	3.600	500	130-1.430	1.650	50	150	1.200	±325	3	71	290	140	332	On request	On request
4,5T160BZ	5.000	500	130-930	1.150	60	150	1.200	±200	3	84	275	144	403	On request	On request
4,5T160BZ	5.000	500	130-1.130	1.350	60	150	1.200	±250	3	84	264	149	421	On request	On request

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	VSmax mm	ISO	V mm	CofG Z mm	CofG Y mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
4,5T160BZ	5.000	500	130-1.230	1.460	60	150	1.200	±275	3	84	258	152	433	On request	On request
4,5T160BZ	5.000	500	130-1.310	1.550	60	150	1.200	±295	3	84	253	154	439	On request	On request
4,5T160BZ	5.000	500	130-1.530	1.750	60	150	1.200	±350	3	84	244	160	458	On request	On request
4,5T160BZ	5.000	500	130-1.630	1.850	60	150	1.200	±375	3	84	240	162	467	On request	On request

4,8T160BZ ¹⁾	5.000	600	130-930	1.150	70	150	1.200	±200	3	84	300	138	444	On request	On request
4,8T160BZ ¹⁾	5.000	600	130-1.130	1.350	70	150	1.200	±250	3	84	291	143	462	On request	On request
4,8T160BZ ¹⁾	5.000	600	130-1.230	1.460	70	150	1.200	±275	3	84	286	147	471	On request	On request
4,8T160BZ ¹⁾	5.000	600	130-1.310	1.550	70	150	1.200	±295	3	84	280	150	480	On request	On request
4,8T160BZ ¹⁾	5.000	600	130-1.530	1.750	70	150	1.200	±350	3	84	271	156	504	On request	On request
4,8T160BZ ¹⁾	5.000	600	130-1.630	1.850	70	150	1.200	±375	3	84	267	158	517	On request	On request

6T160Z	6.000	600	200-1.110	1.350	70	150	1.200	±227,5	4	111	257	192	522	On request	On request
6T160Z	6.000	600	200-1.200	1.460	70	150	1.200	±250	4	111	252	194	534	On request	On request
6T160Z	6.000	600	200-1.400	1.650	70	150	1.200	±300	4	111	245	199	554	On request	On request
6T160Z	6.000	600	200-1.600	1.860	70	150	1.200	±350	4	111	237	204	576	On request	On request

8T160Z	8.000	600	200-1.600	1.860	70	150	1.200	±350	4	111	237	204	576	On request	On request
8T160Z	8.000	600	200-1.800	2.060	70	150	1.200	±400	4	111	230	208	597	On request	On request
8T160Z	8.000	600	200-2.000	2.260	70	150	1.200	±450	4	111	224	212	618	On request	On request
8T160Z	8.000	600	210-2.060	2.400	70	150	1.200	±462,5	4	111	220	214	629	On request	On request

10T160Z	8.000	900	100-1.730	2.060	70	200	1.200	±407,5	4	138	253	212	877	On request	On request
10T160Z	8.000	900	100-1.900	2.260	70	200	1.200	±450	4	138	247	216	905	On request	On request
10T160Z	8.000	900	100-2.000	2.400	70	200	1.200	±475	4	138	243	218	924	On request	On request
10T160Z	8.000	1.100	100-1.730	2.060	80	200	1.200	±407,5	4	138	242	219	900	On request	On request
10T160Z	8.000	1.100	100-1.900	2.260	80	200	1.200	±450	4	138	236	221	928	On request	On request
10T160Z	8.000	1.100	100-2.000	2.400	80	200	1.200	±475	4	138	232	223	947	On request	On request

1) 4,8T with capacity (kg/mm) 2.700/1.200 available upon request.

Not suitable for clamping between the forks.

Available without sideshift.

Load backrest see model T479 and T479.1

with screw-on forks available upon request: ZA-Version
Optional in explosion proof version



Specification:

The KAUP hook-on Fork Positioner T160Z

(A) is an economical Fork Positioner with welded on or screwed on forks offering an excellent view to the fork tips and load. Therefore the achievable residual capacities are very good. The qualities of the range of T160Z (A) Fork Positioners are particularly effective when different sizes of loads are regularly transported or different kinds of transportation are used - for example in logistics.

Qualities:

- For moderately heavy operation
- Excellent residual capacity
- High stability with optimal tare weight
- Very good visibility conditions
- Valve block sideshift serially
- Supplied with welded forks
- Supplied optionally with screw on forks for wear intensive operation (A-version)
- Forks with a length of more than 2400mm available upon request
- Construction width of the attachment and opening range is not dependent on the width of the forklift truck carriage