



## Technical Data

Model	Cap. kg	LCD mm	H-J mm	I mm	E mm	ISO	V mm	CofG Z mm	CofG Z1 mm	Weight kg	Price 人民币	Add-on price per 100mm length 人民币
<b>1T183C</b>	1.500	500	500-1.200	7x100	1.110	2	120	358	--	115	On request	On request
<b>2T183C</b>	2.500	500	500-1.200	7x100	1.080	2	140	368	--	158	On request	On request
<b>2T183C</b>	2.500	500	500-1.200	7x100	1.080	3	140	368	--	158	On request	On request
<b>3T183C</b>	4.000	500	500-1.200	7x100	1.365	3	160	310	--	210	On request	On request
<b>5T183C</b>	6.000	600	600-1.200	4x150	1.255	4	200	359	--	270	On request	On request
<b>7T183C</b>	8.000	600	600-1.200	4x150	1.250	4	260	372	--	262	On request	On request
<b>10T183C</b>	6.600	1.200	1.175-2.000	5x165	1.165	4	260	685	--	585	On request	On request
<b>1T183CTM</b>	820	1.200	1.200-2.000	8x100	1.135	2	120	390	587	150	On request	On request
<b>2T183CTM</b>	1.470	1.200	1.200-2.000	8x100	1.230	2	140	359	537	181	On request	On request
<b>2T183CTM</b>	1.470	1.200	1.200-2.000	8x100	1.230	3	140	359	537	181	On request	On request
<b>3T183CTM</b>	2.350	1.200	1.200-2.000	8x100	1.310	3	160	349	524	245	On request	On request
<b>5T183CTM</b>	3.650	1.350	1.350-2.150	8x100	1.265	4	200	440	663	349	On request	On request
<b>7T183CTM</b>	5.000	1.350	1.350-2.150	8x100	1.265	4	220	433	631	373	On request	On request
<b>1T183CTH</b>	820	1.200	1.200-2.000	-	1.220	2	120	390	609	150	On request	On request
<b>2T183CTH</b>	1.470	1.200	1.200-2.000	-	1.230	2	140	359	570	181	On request	On request
<b>2T183CTH</b>	1.470	1.200	1.200-2.000	-	1.230	3	140	359	570	181	On request	On request

<b>Model</b>	Cap. kg	LCD mm	H-J mm	I mm	E mm	ISO	V mm	CofG Z mm	CofG Z1 mm	Weight kg	Price 人民币	Add-on price per 100mm length 人民币
<b>3T183CTH</b>	2.350	1.200	1.200-2.000	-	1.320	3	160	349	543	245	On request	On request
<b>5T183CTH</b>	3.650	1.350	1.350-2.150	-	1.280	4	200	440	684	349	On request	On request
<b>7T183CTH</b>	5.000	1.350	1.350-2.150	-	1.270	4	260	433	672	373	On request	On request
<b>10T183CTH</b>	6.400	1.350	1.350-2.050	-	1.145	4	260	570	707	820	On request	On request

1) T183C = hook manually adjustable

T183CTM = mechanical telescope

T183CTH = hydraulic telescope - 1 hydraulic function

Higher capacities upon request.



## Crane Jib T183C, T183CTM, T183CTH<sup>1)</sup>

---

---

### Specification:

Different versions of KAUP Crane Jibs are mounted directly onto the fork carriage. Combination with other attachments or with standard forks is, depending on the handling task, easily possible.

Depending on the version chosen, the crane hook can be either adjusted mechanically (T183C), the telescopic boom extended mechanically (T183CTM) or hydraulically (T183CTH).

---

### Qualities:

- Solid construction
- Good visibility conditions
- Simple assembly
- Original forklift truck forks can be used
- Combination with other attachments possible