



Technical Data

Model	Cap. kg	LCD mm	B mm	C mm	D mm	H-J mm	I mm	E mm	ISO	V mm	CofG Z mm	CofG Z1 mm	Weight kg	Price 人民币	Add-on price per 100mm length 人民币
1T183H	1.500	500	125	585	920	500-1.200	7x100	945	2	186	267	--	203	On request	On request
2T183H	2.500	500	132	585	920	500-1.200	7x100	915	2	198	315	--	232	On request	On request
2T183H	2.500	500	142	585	920	500-1.200	7x100	1.015	3	208	293	--	260	On request	On request
3T183H	4.000	500	155	720	1.150	500-1.200	7x100	1.155	3	234	265	--	349	On request	On request
5T183H	6.000	600	187	720	1.220	600-1.200	4x150	950	4	284	268	--	555	On request	On request
2T183HTM	1.530	1.150	132	585	920	1.150-1.950	8x100	1.065	2	198	311	436	252	On request	On request
2T183HTM	1.530	1.150	142	585	920	1.150-1.950	8x100	1.165	3	208	292	403	281	On request	On request
3T183HTM	2.475	1.140	155	720	1.150	1.140-1.940	8x100	1.160	3	234	290	398	386	On request	On request
5T183HTM	3.850	1.280	145	720	1.220	1.280-2.080	8x100	940	4	242	329	469	546	On request	On request
2T183HTH	1.525	1.155	132	585	920	1.155-1.965	-	1.065	2	198	330	471	268	On request	On request
2T183HTH	1.525	1.155	142	585	920	1.155-1.965	-	1.165	3	208	310	437	296	On request	On request
3T183HTH	2.480	1.135	155	720	1.150	1.135-1.945	-	1.160	3	234	332	424	420	On request	On request
5T183HTH	3.910	1.260	145	720	1.220	1.260-2.070	-	950	4	242	370	502	585	On request	On request

1) T183H = hydraulic swivel $\pm 45^\circ$ - hook manually adjustable - 1 hydraulic function

T183HTM = hydraulic swivel $\pm 45^\circ$ and mechanical telescope - 1 hydraulic function

T183HTH = hydraulic swivel $\pm 45^\circ$ and hydraulic telescope - 2 hydraulic functions

Higher capacities available upon request.



Specification:

Different versions of this range of KAUP

Crane Jibs are mounted directly onto the fork carriage. Combination with other attachments or with standard forks is, depending on the handling task, easily possible. The hydraulically swivelling crane column (90° to the right and left) further extends the application possibilities of this attachment. Depending on the version chosen, the crane hook can be either adjusted mechanically (T183H), the telescopic boom extended mechanically (T183HTM) or hydraulically (T183HTH).

Qualities:

- Solid construction
- Good visibility conditions
- Simple assembly
- Original forklift truck forks can be used
- Combination with other attachments possible