



1 hydraulic function

Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	H mm	I mm	K mm	ISO	Md Δ -P = 125 bar Nm	Req. oil volume per rotation ltr.	V mm	CofG Z mm	Weight kg	Price 人民币
1T351.2G	1.800	500	817	890	203	288	33	2	6.013	7,6	207	124	250	On request
2T351.1G	2.500	500	790	1.040	269	515	29	2	7.700	9,7	174	93	302	On request
2T351.1G	2.500	500	790	1.150	269	515	29	2	7.700	9,7	174	95	310	On request
2,5T351.1G	3.200	500	790	1.100	269	515	33	3	7.700	9,7	179	106	387	On request
3,5T351.1G	4.000	500	880	1.100	381	539	36	3	11.815	13,8	202	113	525	On request
4T351.1G	5.000	500	900	1.100	378	595	36	3	14.823	17,4	221	120	575	On request
4,5T351.1G	5.000	500	900	1.350	328	695	40	4	14.823	17,4	231	129	670	On request
5T351.2G	6.000	600	1.080	1.350	351	460	40	4	13.434	15,7	275	167	725	On request
6T351.2G	6.500	600	1.260	1.350	351	460	40	4	17.157	20,7	275	155	842	On request
8T351.2G	8.000	900	1.300	1.600	396	480	40	4	21.679	18,8	304	175	1.080	On request

Rotators with higher rotating speeds available upon request

Other fork carriage widths available upon request.

Lateral supporting fork 1.000 mm (add-on-price)

Lateral supporting fork 1.000 mm (add-on-price)

Rotators up to 40 T upon request.

Matching forks for KAUP-Rotators on request.

When forks are used in combination with a Rotator extremely high strain is applied to the lower fork angle when rotating a load which in turn strains the lower brackets.

For this type of operation KAUP recommends forks with strengthened lower brackets. Strengthened lower brackets can be ordered for all ISO forks model T180.



Rotator 360° endless, foundry version T351G

Specification:

The KAUP Rotator 360° endless T351 is also available in a foundry implementation. This attachment is adapted to the demands of this operational area with a closed fork carriage plate and a closed base plate as well as heat-resistant covered hydraulic tubes. Otherwise this rotator resembles the T351.

Qualities:

- Foundry implementation
- Good residual capacity
- Rotation 360° endlessly
- Robust construction with gear drive
- Original forks usable Lateral supporting fork and load stabilizers optionally