



with independent sideshift - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
1T411Z	1.500	500	±100	340-1.300	750	40	100	1.200	2	133	268	237	On request	On request
1T411Z	1.500	500	±100	340-1.520	970	40	100	1.200	2	133	251	259	On request	On request
1T411Z	1.500	500	±100	350-1.700	1.130	40	100	1.200	2	133	244	270	On request	On request
1T411Z	1.500	500	±100	330-1.730	1.200	40	100	1.200	2	133	241	274	On request	On request
1,6T411Z	2.300	500	±100	290-1.470	1.040	45	120	1.200	2	133	266	331	On request	On request
1,6T411Z	2.300	500	±100	320-1.620	1.130	45	120	1.200	2	133	262	337	On request	On request
1,6T411Z	2.300	500	±100	320-1.820	1.330	45	120	1.200	2	133	255	351	On request	On request
1,6T401Z	2.300	500	-	300-1.300	850	45	120	1.200	2	126	277	310	On request	On request
2,5T411Z	2.800	500	±100	290-1.470	1.040	50	120	1.200	2	143	272	360	On request	On request
2,5T411Z	2.800	500	±100	320-1.620	1.130	50	120	1.200	2	143	269	367	On request	On request
2,5T411Z	2.800	500	±100	320-1.820	1.330	50	120	1.200	2	143	262	379	On request	On request
2,5T401Z	2.800	500	-	300-1.300	850	50	120	1.200	2	136	285	330	On request	On request
2,5T411Z	3.000	500	±100	320-1.620	1.130	50	120	1.200	3	143	253	390	On request	On request
2,5T411Z	3.000	500	±100	320-1.820	1.330	50	120	1.200	3	143	247	402	On request	On request
3T411Z	3.600	500	±100	260-1.560	1.130	50	150	1.200	2	152	259	495	On request	On request
3T411Z	3.600	500	±100	260-1.760	1.330	50	150	1.200	2	152	253	513	On request	On request
3T411Z	3.600	500	±100	130-1.630	1.460	50	150	1.200	2	152	250	522	On request	On request

Model	Cap. kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
3T411Z	3.600	500	±100	250-1.870	1.460	50	150	1.200	2	152	249	524	On request	On request
3T411Z	3.600	500	±100	260-1.560	1.130	50	150	1.200	3	152	259	495	On request	On request
3T411Z	3.600	500	±100	260-1.760	1.330	50	150	1.200	3	152	253	513	On request	On request
3T411Z	3.600	500	±100	130-1.630	1.460	50	150	1.200	3	152	250	522	On request	On request
3T411Z	3.600	500	±100	250-1.870	1.460	50	150	1.200	3	152	249	524	On request	On request

4T411Z	4.150	500	±100	260-1.560	1.130	50	150	1.200	3	162	248	559	On request	On request
4T411Z	4.150	500	±100	260-1.760	1.330	50	150	1.200	3	162	243	578	On request	On request
4T411Z	4.150	500	±100	130-1.630	1.460	50	150	1.200	3	162	240	589	On request	On request
4T411Z	4.150	500	±100	250-1.870	1.460	50	150	1.200	3	162	239	591	On request	On request

4,5T411Z	5.000	500	±100	280-1.630	1.200	60	150	1.200	3	188	258	652	On request	On request
4,5T411Z	5.000	500	±100	240-1.680	1.330	60	150	1.200	3	188	254	667	On request	On request
4,5T411Z	5.000	500	±100	270-1.870	1.460	60	150	1.200	3	188	250	682	On request	On request
4,5T411Z	5.000	500	±100	280-1.980	1.550	60	150	1.200	3	188	248	695	On request	On request

4,5T411Z.1	5.000	500	±100	280-1.630	1.200	60	150	1.200	3	178	256	650	On request	On request
4,5T411Z.1	5.000	500	±100	240-1.680	1.330	60	150	1.200	3	178	252	664	On request	On request
4,5T411Z.1	5.000	500	±100	270-1.870	1.460	60	150	1.200	3	178	249	679	On request	On request
4,5T411Z.1	5.000	500	±100	280-1.980	1.550	60	150	1.200	3	178	246	690	On request	On request

4,8T411Z	5.000	600	±100	280-1.630	1.200	70	150	1.200	3	178	280	696	On request	On request
4,8T411Z	5.000	600	±100	240-1.680	1.330	70	150	1.200	3	178	277	710	On request	On request
4,8T411Z	5.000	600	±100	270-1.870	1.460	70	150	1.200	3	178	273	725	On request	On request
4,8T411Z	5.000	600	±100	280-1.980	1.550	70	150	1.200	3	178	270	736	On request	On request

5T411Z	6.200	600	±160	190-1.690	1.460	70	150	1.200	4	176	250	807	On request	On request
5T411Z	6.200	600	±160	230-1.860	1.550	70	150	1.200	4	176	247	819	On request	On request
5T411Z	6.200	600	±160	500- 2.400 ¹⁾	1.550	70	150	1.200	4	176	239	879	On request	On request
5T411Z	6.200	600	±160	230-2.130	1.820	70	150	1.200	4	176	241	850	On request	On request

1) Transport of europallets lengthwise not possible.
Not suitable for clamping between the forks.
with screw-on forks available upon request: T411 ZA
Also available without sideshift, model T401Z
Load Backrest see model T179.



Specification:

The KAUP hook-on Fork Positioner T411Z

is a robust attachment for exceptionally heavy duty operation - ideal for uneven surfaces. Spreading forces induced, for example when handling coils (several) cable drums, rolls or wire coils, can readily be supported due to the large overlap of sectional profiles between fork guide and clamp body. Speedy working cycles and millimetre accurate positioning of the transport load is possible.

Qualities:

- Good residual capacity

- Good visibility conditions
- Independent sideshift serially - alternatively valve block sideshift
- Opening range significantly larger than the construction width
- Use of longer forks possible