



with independent sideshift - with cylinder- and sideshift protection - 2 hydraulic functions

## Technical Data

Model	Cap. kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	CofG <sub>v</sub> Y mm	Weight kg	Price 人民币
2T413RC	2.100	500	±100	575-1.875	1.040	440	42	1.000	2	143	280	210	573	On request
2T413RC	2.100	500	±100	575-1.875	1.040	440	42	1.200	2	143	346	212	628	On request
2T413RC	2.100	500	±100	575-1.875	1.040	440	42	1.000	3	143	280	210	573	On request
2T413RC	2.100	500	±100	575-1.875	1.040	440	42	1.200	3	143	346	212	628	On request
2T413RC	2.100	500	±100	485-1.785	1.130	440	42	1.000	2	143	277	209	580	On request
2T413RC	2.100	500	±100	485-1.785	1.130	440	42	1.200	2	143	343	211	635	On request
2T413RC	2.100	500	±100	485-1.785	1.130	440	42	1.000	3	143	277	209	580	On request
2T413RC	2.100	500	±100	485-1.785	1.130	440	42	1.200	3	143	343	211	635	On request
2T413RC	2.100	500	±100	595-2.395	1.520	440	42	1.000	2	143	258	214	641	On request
2T413RC	2.100	500	±100	595-2.395	1.520	440	42	1.200	2	143	319	215	696	On request
2T413RC	2.100	500	±100	595-2.395	1.520	440	42	1.000	3	143	258	214	641	On request
2T413RC	2.100	500	±100	595-2.395	1.520	440	42	1.200	3	143	319	215	696	On request

3T413RC	1.790	700	±100	465-1.765	1.130	500	130	1.400	2	153	371	221	811	On request
3T413RC	1.560	800	±100	465-1.765	1.130	500	130	1.600	2	153	422	217	847	On request
3T413RC	1.790	700	±100	465-1.765	1.130	500	130	1.400	3	153	371	221	811	On request
3T413RC	1.560	800	±100	465-1.765	1.130	500	130	1.600	3	153	422	217	847	On request
3T413RC	1.790	700	±100	605-2.235	1.330	500	130	1.400	2	153	361	221	840	On request
3T413RC	1.560	800	±100	605-2.235	1.330	500	130	1.600	2	153	410	217	875	On request
3T413RC	1.790	700	±100	605-2.235	1.330	500	130	1.400	3	153	361	221	840	On request
3T413RC	1.560	800	±100	605-2.235	1.330	500	130	1.600	3	153	410	217	875	On request

4T413RC	2.140	700	±100	565-1.965	1.130	500	130	1.400	3	163	370	257	919	On request
4T413RC	1.880	800	±100	565-1.965	1.130	500	130	1.600	3	163	419	252	955	On request
4T413RC	2.140	700	±100	595-2.225	1.330	500	130	1.400	3	163	354	260	975	On request
4T413RC	1.880	800	±100	595-2.225	1.330	500	130	1.600	3	163	401	255	1.011	On request

4,5T413RC	2.400	800	±100	550-1.950	1.200	500	130	1.600	3	188	391	220	1.025	On request
4,5T413RC	1.920	1.000	±100	550-1.950	1.200	500	130	2.000	3	188	489	214	1.095	On request
4,5T413RC	2.400	800	±100	650-2.280	1.330	500	130	1.600	3	188	383	220	1.051	On request
4,5T413RC	1.920	1.000	±100	650-2.280	1.330	500	130	2.000	3	188	479	214	1.122	On request

Model	Cap. kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	CofG Y mm	Weight kg	Price 人民币
<b>4,5T413RC</b>	2.400	800	±100	590-2.290	1.460	500	130	1.600	3	188	377	220	1.072	On request
<b>4,5T413RC</b>	1.920	1.000	±100	590-2.290	1.460	500	130	2.000	3	188	471	214	1.142	On request
<b>4,5T413RC</b>	2.400	800	±100	630-2.460	1.550	500	130	1.600	3	188	372	220	1.092	On request
<b>4,5T413RC</b>	1.920	1.000	±100	630-2.460	1.550	500	130	2.000	3	188	465	214	1.162	On request

Also available without sideshift, model T403RC

Load Backrest see model T179.



### Specification:

KAUP Recycling Clamps are suitable for the transportation of non-palletised reusable materials in the recycling industry. This special range of bale clamps has several specific features, e.g. clamping arms 2 metres long for clamping the load, strengthened arm connections on the clamp profiles to allow clamping with the tips of the arms.

### Qualities:

- Excellent price-performance ratio
- Solid strengthened design with KAUP clamp profiles from T-profiles and C-profiles
- Strengthened arm construction with toothed bars
- Solid wear and tear bars under clamp body and clamp arms optionally
- Separate sideshifter
- Combination with KAUP rotary devices possible
- Customer specified modifications feasible