



with independent sideshift - for cylindrical steel drums - 2 hydraulic functions, This Drum Clamp can transport 2 or 4 drums palletless and safely.

## Technical Data

Model	Number of drums	Cap. kg	LCD mm	S mm	A mm	B mm	C mm	F mm	ISO	V mm	CofG Z mm	CofG <sub>v</sub> Y mm	Weight kg	Price 人民币
1,5T415-2	2-4	1.250	630	±100	370-1.550	970	1.105	195	2	133	255	266	310	On request
1,5T415-2	2-4	1.250	630	±100	370-1.550	970	1.105	195	3	133	255	266	310	On request
2T415-2	2-4	2.000	630	±100	370-1.670	1.130	1.105	195	2	143	245	264	350	On request
2T415-2	2-4	2.000	630	±100	370-1.670	1.130	1.105	195	3	143	245	264	350	On request

The arms are coated with Remagrip (see coatings in the pricelist).

Fitted with pressure reduction and manometer gauge.C1160

Available with arms for plastic drums upon request.

This version is for cylindric drums with diameter of 600 mm. For other diameters on request.

Also available without sideshift, model T405-2

Load Backrest see model T179.



## Drum Clamp T415-2

---

---

### Specification:

The KAUP Drum Clamp T415-2 can transport two (one in front of the other) or four drums (pre and side by side) safely and without palettes. Therefore the clamp arms are serially vulcanised with rubber.

---

### Qualities:

- Low lost load - good residual capacity
- Good visibility conditions
- Stable construction
- Independent sideshift serially