



with independent sideshift - with bolt-on forks, for 1, 2 or 3 pallets side by side - 2 hydraulic functions¹⁾

Technical Data

Model	Pallet handling	Cap. kg	LCD mm	For FLT max.	S mm	B mm	A mm	C mm	E mm	D mm	F mm	G mm	I mm	ISO	V mm	CofG Z mm	CofG _v Y mm	Weight kg	Price 人民币
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.460	560	1.580	2.210	570	510	1.150	50	2	170	227	275	712	On request
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.460	560	1.580	2.210	570	510	1.150	50	3	170	227	275	712	On request
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.660	560	1.580	2.410	570	510	1.150	50	2	170	221	277	739	On request
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.660	560	1.580	2.410	570	510	1.150	50	3	170	221	277	739	On request
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.760	560	1.580	2.510	570	510	1.150	50	2	170	219	278	752	On request
3T429B-1-2-3	800x1200	3.000	600	3,5/500	±100	1.760	560	1.580	2.510	570	510	1.150	50	3	170	219	278	752	On request
3T429B-1-2-3	1000x1200	3.000	600	3,5/500	±100	1.960	660	1.900	2.910	680	620	1.150	50	2	170	213	273	781	On request
3T429B-1-2-3	1000x1200	3.000	600	3,5/500	±100	1.960	660	1.900	2.910	680	620	1.150	50	3	170	213	273	781	On request
4T429B-1-2-3	800x1200	3.800	600	5,0/500	±100	1.460	560	1.580	2.210	570	510	1.150	60	3	170	244	268	761	On request
4T429B-1-2-3	800x1200	3.800	600	5,0/500	±100	1.660	560	1.580	2.410	570	510	1.150	60	3	170	238	270	787	On request
4T429B-1-2-3	800x1200	3.800	600	5,0/500	±100	1.760	560	1.580	2.510	570	510	1.150	60	3	170	236	271	800	On request
4T429B-1-2-3	1000x1200	3.800	600	5,0/500	±100	1.960	660	1.900	2.910	680	620	1.150	60	3	170	230	273	829	On request
4T429B-1-2-3	1200x1000	3.800	600	5,0/500	±100	2.150	670	1.910	3.120	680	620	1.000	60	3	170	193	283	851	On request
5T429B-1-2-3	800x1200	4.500	600	6,0/600	±160	1.460	560	1.580	2.210	570	510	1.150	60	4	190	243	321	861	On request
5T429B-1-2-3	800x1200	4.500	600	6,0/600	±160	1.660	560	1.580	2.410	570	510	1.150	60	4	190	238	323	890	On request

Model	Pallet handling	Cap. kg	LCD mm	For FLT max.	S mm	B mm	A mm	C mm	E mm	D mm	F mm	G mm	I mm	ISO	V mm	CofG Z mm	CofG Y mm	Weight kg	Price 人民币
5T429B-1-2-3	1000x1200	4.500	600	6,0/600	±160	1.960	660	1.900	2.910	680	620	1.150	60	4	190	231	327	935	On request
5T429B-1-2-3	1200x1000	4.500	600	6,0/600	±160	2.150	670	1.910	3.120	680	620	1.000	60	4	190	199	341	954	On request

1) Solenoid valve for individual control of pallets left and right. (add-on-price)

Fork length optional 1200 mm, 1150 mm or 1000 mm.

Locating claw on fork tip available upon request. Wider fork shanks available upon request.



Specification:

The simple construction of KAUP Triple

Pallet Handler T429B-1-2-3 with innovated visibility improved design ensures a clear view through and over the attachment to the fork tips and load. The practice orientated construction from T-profiles and C-profiles ensures highest stability and long operating hours with extended intervals between servicing and a minimum of required maintenance even in heavy duty operation. The excellent residual capacity compared to similar models increases the productivity of this Multi Pallet Handler even more.

Qualities:

- Triple Pallet Handlers for heavy duty tasks
- Very good visibility conditions
- Excellent residual capacity - best lost load centre in this class
- Synchronized for quicker working speeds
- Independent sideshift serially

- Screw-on forks serially
- Optional: independent control of separate fork pairs - adjustment of opening range to suit different types of pallets