Double Pallet Handler T429C (10.11.2026)

with separate sideshift -

with screw-on forks - for 1 or 2 pallets side by side, Model T429-4 for 2 pallets in front of each other or 4 pallets in front and next to each other - 2 hydraulic functions

Model	Cap. kg	LCD mm	S mm	A mm	B mm	D mm	E mm	H mm	G mm	ISO	V mm	CofG Z mm	CofG$_V$ Y mm	Weight kg	Price 人民币
1,5T429C	**1.600**	**600**	**±100**	**560-1.720**	**930**	**40**	**80**	**1.400**	**1.150**	**2**	**145**	**228**	**241**	**438**	**On request**
2T429C	2.200	600	±100	560-1.960	1.200	40	80	1.400	1.150[2)]	2	145	216	245	470	On request
2T429C	**2.500**	**600**	**±100**	**560-1.960**	**1.200**	**50[1)]**	**80**	**1.400**	**1.150[2)]**	**2**	**145**	**242**	**239**	**518**	**On request**
2T429C	**2.500**	**600**	**±100**	**560-1.960**	**1.200**	**50[1)]**	**80**	**1.400**	**1.150[2)]**	**3**	**145**	**238**	**246**	**527**	**On request**
2T429C	**2.500**	**600**	**±100**	**560-2.160**	**1.400**	**50[1)]**	**80**	**1.400**	**1.150[2)]**	**2**	**145**	**236**	**240**	**536**	**On request**
2T429C	**2.500**	**600**	**±100**	**560-2.160**	**1.400**	**50[1)]**	**80**	**1.400**	**1.150[2)]**	**3**	**145**	**232**	**247**	**545**	**On request**
2T429C-4	1.250	1.200	±100	560-1.960	1.200	50	80	1.400	2.400	2	145	550	181	650	On request
2T429C-4	1.250	1.200	±100	560-1.960	1.200	50	80	1.400	2.400	3	145	543	188	660	On request
2,5T429C-4	1.600	1.200	±100	560-1.960	1.200	60	80	1.400	2.400	3	145	577	181	730	On request
3T429C	**3.200**	**600**	**±100**	**560-1.960**	**1.200**	**60**	**80**	**1.400**	**1.150[2)]**	**3**	**145**	**256**	**241**	**572**	**On request**
3T429C	**3.200**	**600**	**±100**	**560-2.160**	**1.400**	**60**	**80**	**1.400**	**1.150[2)]**	**3**	**145**	**250**	**243**	**590**	**On request**
3T429C-2[3)]	**5.000**	**600**	**±100**	**560-1.960**	**1.200**	**60**	**80**	**1.400**	**1.150[2)]**	**3**	**180**	**246**	**287**	**720**	**On request**
3T429C-2[3)]	**5.000**	**600**	**±100**	**560-1.960**	**1.200**	**60**	**80**	**1.400**	**1.150[2)]**	**4**	**183**	**238**	**288**	**749**	**On request**
3T429C-2	5.000	600	±100	560-1.960	1.400	60	80	1.400	1.150[2)]	3	180	240	289	748	On request
3T429C-2	5.000	600	±100	560-1.960	1.400	60	80	1.400	1.150[2)]	4	183	233	290	777	On request
3T429C-4[3)]	**2.500**	**1.200**	**±100**	**560-1.960**	**1.200**	**60**	**80**	**1.400**	**2.400**	**3**	**180**	**578**	**220**	**910**	**On request**
3T429C-4[3)]	**2.500**	**1.200**	**±100**	**560-1.960**	**1.200**	**60**	**80**	**1.400**	**2.400**	**4**	**183**	**561**	**212**	**940**	**On request**
3T429C-4	2.500	1.200	±100	560-1.960	1.400	60	80	1.400	2.400	3	180	563	223	933	On request
3T429C-4	2.500	1.200	±100	560-1.960	1.400	60	80	1.400	2.400	4	183	550	215	963	On request
3,5T429C-4[3)]	2.800	1.200	±100	560-1.960	1.200	60	80	1.400	2.400	3	180	568	221	941	On request
3,5T429C-4[3)]	2.800	1.200	±100	560-1.960	1.200	60	80	1.400	2.400	4	183	561	212	941	On request
3,5T429C-4	2.800	1.200	±100	560-1.960	1.400	60	80	1.400	2.400	3	180	556	224	964	On request
3,5T429C-4	2.800	1.200	±100	560-1.960	1.400	60	80	1.400	2.400	4	183	550	215	964	On request
4T429C-4[4)]	3.200	1.200	±160	560-1.960	1.460	60	80	1.400	2.400	4	183	512	237	1.038	On request
4T429C-4[4)]	**4.600**	**1.200**	**±160**	**560-1.960**	**1.460**	**70**	**80**	**1.400**	**2.400**	**4**	**183**	**536**	**228**	**1.111**	**On request**
6T429-4[4)]	6.000	1.200	±160	560-1.960	1.860	75	90	1.400	2.400	4	218	530	205	1.390	On request
6T429-4[4)]	6.000	1.200	±250	560-1.960	1.920	75	90	1.400	2.400	4	218	530	205	1.410	On request

Measurement „C" = alternatively 560 / 650 / 700 mm mechanically or hydraulically adjustable (solenoid valve required).
Measurement „H" = standard height 1.400 mm, other lengths and forms upon request.
Double solenoid valve for additional individual adjustment for each pair of forks available upon request. (add-on price)
1) Optional with fork thickness 40 mm. (add-on price)
2) Fork length optional 1.000 mm, 1.150 mm or 1.200 mm. (no add-on price)
3) for handling of europallets crosswise we recommend the 1.400 mm wide body version
4) Standard with wider fork shanks.
Locating claw on fork tip available upon request.
Double Pallet Handler with Load Stabilizer available upon request.

Double Pallet Handler T429C