



Rotation 360° continuous - with additional pair of forks to empty various boxes - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	E1 mm	D1 mm	G1 mm	E2 mm	D2 mm	G2 mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
1,5T451W/180	1.250	500	540- 1.720	970	125	45	1.200	125	45	1.200	6.013	7,6	2B	267	431	678	On request
1,5T451W/180	1.250	500	530- 1.930	1.200	125	45	1.200	125	45	1.200	6.013	7,6	2B	267	425	694	On request
2T451W/180	2.000	500	560- 1.860	1.130	150	50	1.200	150	50	1.200	7.700	9,7	2B	285	437	905	On request
2T451W/180	2.000	500	560- 2..060	1.330	150	50	1.200	150	50	1.200	7.700	9,7	2B	285	432	920	On request
2T451W/180	2.000	500	560- 1.860	1.130	150	50	1.200	150	50	1.200	7.700	9,7	3B	285	437	905	On request
2T451W/180	2.000	500	560- 2..060	1.330	150	50	1.200	150	50	1.200	7.700	9,7	3B	285	432	920	On request
3T451W/180	2.500	500	560- 1.860	1.130	150	50	1.200	150	50	1.200	8.950	11,3	3B	333	423	1.083	On request
3T451W/180	2.500	500	560- 2..060	1.330	150	50	1.200	150	50	1.200	8.950	11,3	3B	333	419	1.102	On request

Attention: Additional forks exclusively possible with underclearance according to ISO class »B« version

Note: Container must have suitable insertion slots.

Also available with sideshift, model T491W/180 on request



Pallet Turnover Clamp T451W/180

Specification:

An additional fork pair distinguishes

this attachment from the Pallet Turnover Clamp T451. It allows an easy

and safe emptying of the most different transport containers or grid

boxing with suitable insertion slots.

Qualities:

- Good visibility conditions
- Stable construction
- Rotation 360° endlessly
- Two double forks with additional fork pair serially for safe handling
- Optionally with sideshift available