



Rotation 360° continuous - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	H mm	I mm	K mm	Md Δ -P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
2T456BZ	2.500	500	130-930	1.150	45	120	1.200	269	457	33	7.700	9,7	2	210	261	455	On request
2T456BZ	2.500	500	130-930	1.150	45	120	1.200	269	457	33	7.700	9,7	3	210	261	455	On request
3,5T456BZ	3.600	500	130-930	1.150	50	150	1.200	338	395	40	8.950	11,3	3	258	271	703	On request
4,5T456BZ	4.500	500	130-1.130	1.350	60	150	1.200	338	395	40	8.950	11,3	3	261	279	788	On request
5T456BZ	5.000	600	260-1.260	1.700	60	150	1.200	351	445	40	13.434	15,7	4	334	309	980	On request

Md: Torque at dP = 125 bar.

Larger models and different widths available upon request.

Also available with bolt-on forks: T456BZA

Also available with sideshift, model T496BZ on request



Specification:

This attachment combines the advantages of two KAUP series: Rotators and Fork Positioners. With the 1000-fold proven basic components of the KAUP modular system the result is a robust device with numerous different application possibilities.

Qualities:

- Good visibility conditions
- Rotation 360° endless
- Solid construction
- Attachment also available with screw-on forks
- Optionally available with sideshift
- Larger models and construction widths optionally available