



Rotation 360° continuous - 2 hydraulic functions

Technical Data

| Model | Cap. kg | LCD mm | A mm | B mm | D mm | E mm | G mm | H mm | I mm | K mm | Md Δ -P = 125 bar Nm | Req. oil volume per rotation ltr. | ISO | V mm | CofG Z mm | CofG _v Y mm | Weight kg | Price 人民币 |
|-------------------|------------|-----------|---------------|---------|---------|---------|---------|---------|---------|---------|-----------------------------------|--|-----|---------|-----------------|------------------------------|--------------|---------------|
| 2T456BZG | 2.500 | 500 | 130- 930 | 1.150 | 45 | 120 | 1.200 | 269 | 457 | 33 | 7.700 | 9,7 | 2 | 230 | 247 | 216 | 542 | On request |
| 2T456BZG | 2.500 | 500 | 130- 930 | 1.150 | 45 | 120 | 1.200 | 269 | 457 | 33 | 7.700 | 9,7 | 3 | 230 | 247 | 216 | 542 | On request |
| 3,5T456BZG | 3.600 | 500 | 130- 930 | 1.150 | 50 | 150 | 1.200 | 338 | 395 | 40 | 8.950 | 11,3 | 3 | 258 | 273 | 235 | 712 | On request |
| 4,5T456BZG | 4.500 | 500 | 130- 1.130 | 1.350 | 60 | 150 | 1.200 | 338 | 395 | 40 | 8.950 | 11,3 | 3 | 261 | 282 | 231 | 795 | On request |
| 5T456ZG | 5.000 | 600 | 260- 1.260 | 1.700 | 60 | 150 | 1.200 | 345 | 445 | 40 | 13.434 | 15,7 | 4 | 345 | 313 | 281 | 1.014 | On request |
| 8T456ZG | 5.500 | 810 | 240- 1.240 | 1.700 | 70 | 160 | 1.200 | 396 | 480 | 40 | 21.679 | 18,8 | 4 | 402 | 318 | 334 | 1.705 | On request |

Md: Torque at $dP = 125$ bar.

Larger models and different widths available upon request.

Also available with bolt-on forks:T456ZAG

Also available with sideshift, model T496ZG on request



Rotating Fork Positioner foundry version T456ZG

Specification:

The design is, in principle, the same as the normal T456BZ version, the foundry version of this attachment range is suitable for applications with extremely high working temperatures as found, for example, in steel works. Compared to the T456BZ, the KAUP Rotating Fork Positioner T456ZG has a closed front plate and basic plate as well as heat resistant coated hydraulic pipes.

Qualities:

- Attachment also available with screw-on forks
- Solid construction
- Rotation 360° endless
- Optionally available with sideshift
- Larger models and construction widths optionally available