

- short arm adjustable in 45° position - split contact pads - 2 hydraulic functions

## Technical Data

| Model             | Cap.<br>kg | LCD<br>mm | A1-<br>A2<br>mm | F<br>mm | G<br>mm | K<br>mm | L<br>mm | M<br>mm | N<br>mm | Md Δ-P =<br>125 bar<br>Nm | Req. oil volume<br>per rotation<br>ltr. | ISO | V<br>mm | CofG<br>Z<br>mm | Weight<br>kg | Price<br>人民币 | Add-on<br>price f. c-<br>pads w.<br>coating<br>人民币 |
|-------------------|------------|-----------|-----------------|---------|---------|---------|---------|---------|---------|---------------------------|---|-----|---------|-----------------|--------------|--------------|--|
| <b>1T458B-2</b>   | 1.200      | 675       | 200-1.350       | 300     | 700     | 250     | 33      | 208     | 100     | 6.013                     | 7,6                                     | 2   | 185     | 269             | 393          | On request   | On request   |
| <b>1T458B-2</b>   | 1.100      | 725       | 220-1.450       | 300     | 700     | 250     | 33      | 208     | 100     | 6.013                     | 7,6                                     | 2   | 185     | 291             | 406          | On request   | On request   |
| <b>1,5T458B-2</b> | 1.550      | 675       | 200-1.350       | 300     | 700     | 250     | 33      | 208     | 100     | 6.013                     | 7,6                                     | 2   | 185     | 272             | 398          | On request   | On request   |
| <b>1,5T458B-2</b> | 1.500      | 725       | 220-1.450       | 300     | 700     | 250     | 33      | 208     | 100     | 6.013                     | 7,6                                     | 2   | 185     | 285             | 411          | On request   | On request   |
| <b>2T458B-2</b>   | 2.400      | 675       | 200-1.350       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 2   | 207     | 273             | 530          | On request   | On request   |
| <b>2T458B-2</b>   | 2.200      | 725       | 220-1.450       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 2   | 207     | 285             | 542          | On request   | On request   |
| <b>2T458B-2</b>   | 2.000      | 800       | 220-1.600       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 2   | 207     | 304             | 576          | On request   | On request   |
| <b>2T458B-2</b>   | 1.700      | 915       | 350-1.830       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 2   | 207     | 344             | 623          | On request   | On request   |
| <b>2T458B-2</b>   | 2.400      | 675       | 200-1.350       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 3   | 212     | 273             | 530          | On request   | On request   |
| <b>2T458B-2</b>   | 2.200      | 725       | 220-1.450       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 3   | 212     | 285             | 542          | On request   | On request   |
| <b>2T458B-2</b>   | 2.000      | 800       | 220-1.600       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 3   | 212     | 304             | 576          | On request   | On request   |
| <b>2T458B-2</b>   | 1.700      | 915       | 350-1.830       | 340     | 850     | 250     | 33      | 270     | 170     | 7.700                     | 9,7                                     | 3   | 212     | 344             | 623          | On request   | On request   |
| <b>3T458B-2</b>   | 3.200      | 675       | 220-1.350       | 340     | 850     | 250     | 36      | 339     | 170     | 8.950                     | 11,3                                    | 3   | 242     | 260             | 703          | On request   | On request   |
| <b>3T458B-2</b>   | 3.000      | 725       | 250-1.450       | 340     | 850     | 250     | 36      | 339     | 170     | 8.950                     | 11,3                                    | 3   | 242     | 274             | 721          | On request   | On request   |
| <b>3T458B-2</b>   | 2.800      | 800       | 250-1.600       | 340     | 850     | 250     | 36      | 339     | 170     | 8.950                     | 11,3                                    | 3   | 242     | 286             | 749          | On request   | On request   |
| <b>3T458B-2</b>   | 2.500      | 915       | 300-1.830       | 340     | 850     | 250     | 36      | 339     | 170     | 8.950                     | 11,3                                    | 3   | 242     | 303             | 778          | On request   | On request   |
| <b>3T458B-2</b>   | 2.100      | 1100      | 800-2.200       | 340     | 850     | 250     | 36      | 339     | 170     | 8.950                     | 11,3                                    | 3   | 242     | 355             | 868          | On request   | On request   |
| <b>4T458B-2</b>   | 3.900      | 675       | 250-1.350       | 420     | 1.000   | 300     | 36      | 383     | 160     | 12.591                    | 11,2                                    | 3   | 270     | 319             | 991          | On request   | On request   |
| <b>4T458B-2</b>   | 3.700      | 725       | 250-1.450       | 420     | 1.000   | 300     | 36      | 383     | 160     | 12.591                    | 11,2                                    | 3   | 270     | 323             | 1.024        | On request   | On request   |
| <b>4T458B-2</b>   | 3.500      | 800       | 250-1.600       | 420     | 1.000   | 300     | 36      | 383     | 160     | 12.591                    | 11,2                                    | 3   | 270     | 329             | 1.073        | On request   | On request   |

| Model    | Cap.<br>kg | LCD<br>mm | A1-<br>A2<br>mm | F<br>mm | G<br>mm | K<br>mm | L<br>mm | M<br>mm | N<br>mm | Md $\Delta$ -P =<br>125 bar<br>Nm | Req. oil volume<br>per rotation<br>ltr. | ISO | V<br>mm | CofG<br>Z<br>mm | Weight<br>kg | Price<br>人民币  | Add-on<br>price f. c-<br>pads w.<br>coating<br>人民币 |
|----------|------------|-----------|-----------------|---------|---------|---------|---------|---------|---------|-----------------------------------|---|-----|---------|-----------------|--------------|---------------|--|
| 4T458B-2 | 3.400      | 915       | 350-<br>1.830   | 420     | 1.000   | 300     | 36      | 383     | 160     | 12.591                            | 11,2                                    | 3   | 255     | 355             | 1.119        | On<br>request | On request   |
| 4T458B-2 | 2.800      | 1100      | 800-<br>2.200   | 420     | 1.000   | 300     | 36      | 383     | 160     | 12.591                            | 11,2                                    | 3   | 255     | 404             | 1.182        | On<br>request | On request   |
| 4T458B-2 | 3.900      | 675       | 250-<br>1.350   | 420     | 1.000   | 300     | 36      | 351     | 160     | 12.591                            | 11,2                                    | 4   | 270     | 319             | 991          | On<br>request | On request   |
| 4T458B-2 | 3.700      | 725       | 250-<br>1.450   | 420     | 1.000   | 300     | 36      | 351     | 160     | 12.591                            | 11,2                                    | 4   | 270     | 323             | 1.024        | On<br>request | On request   |
| 4T458B-2 | 3.500      | 800       | 250-<br>1.600   | 420     | 1.000   | 300     | 36      | 351     | 160     | 12.591                            | 11,2                                    | 4   | 270     | 329             | 1.073        | On<br>request | On request   |
| 4T458B-2 | 3.400      | 915       | 350-<br>1.830   | 420     | 1.000   | 300     | 36      | 351     | 160     | 12.591                            | 11,2                                    | 4   | 255     | 355             | 1.119        | On<br>request | On request   |
| 4T458B-2 | 2.800      | 1100      | 800-<br>2.200   | 420     | 1.000   | 300     | 36      | 351     | 160     | 12.591                            | 11,2                                    | 4   | 255     | 404             | 1.182        | On<br>request | On request   |

|          |       |      |               |     |       |     |    |     |     |        |      |   |     |     |       |               |            |
|----------|-------|------|---------------|-----|-------|-----|----|-----|-----|--------|------|---|-----|-----|-------|---------------|------------|
| 5T458B-2 | 4.750 | 800  | 250-<br>1.600 | 420 | 1.000 | 300 | 40 | 350 | 160 | 12.591 | 11,2 | 4 | 320 | 373 | 1.200 | On<br>request | On request |
| 5T458B-2 | 4.200 | 915  | 350-<br>1.830 | 420 | 1.000 | 300 | 40 | 350 | 160 | 12.591 | 11,2 | 4 | 315 | 389 | 1.211 | On<br>request | On request |
| 5T458B-2 | 3.900 | 1000 | 500-<br>2.000 | 420 | 1.000 | 300 | 40 | 350 | 160 | 12.591 | 11,2 | 4 | 315 | 436 | 1.241 | On<br>request | On request |
| 5T458B-2 | 3.300 | 1200 | 650-<br>2.400 | 420 | 1.000 | 300 | 40 | 350 | 160 | 12.591 | 11,2 | 4 | 315 | 450 | 1.330 | On<br>request | On request |

|          |       |      |               |     |       |     |    |     |     |        |      |   |     |     |       |               |            |
|----------|-------|------|---------------|-----|-------|-----|----|-----|-----|--------|------|---|-----|-----|-------|---------------|------------|
| 6T458B-2 | 5.500 | 900  | 400-<br>1.800 | 420 | 1.000 | 300 | 40 | 350 | 160 | 19.998 | 17,9 | 4 | 327 | 390 | 1.411 | On<br>request | On request |
| 6T458B-2 | 4.600 | 1100 | 600-<br>2.200 | 420 | 1.000 | 300 | 40 | 350 | 160 | 19.998 | 17,9 | 4 | 327 | 422 | 1.527 | On<br>request | On request |

1) Version with fixed short arm

Contact pads: 1T-3T with polyurethane coating, 4T and above with rubber coating

Capacity related to max. roll diameter.

The short arm is hydraulically adjustable in 45° position.

Optional: restricted to 180° rotation, Tissue version, short arm with continuous contact pads.

For taking up horizontal rolls, 5-degree mast forward tilt is required.

For contact pad coatings see accessories in the pricelist.

Attachment with sideshift Model T498B-2 (add-on price).



## Rotating Roll Clamp T458B-2

---

---

---