Rotating Roll Clamp T458B (10.11.2026)

360° rotation continuous

- short arm adjustable in 45° position - 2 hydraulic functions

Model	Cap. kg	LCD mm	A1-A2 mm	F mm	G mm	K mm	L mm	M mm	N mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofGZ mm	Weight kg	Price 人民币	Add-on price f. c-pads w. coating 人民币
1T458B	1.200	675	200-1.350	300	700	250	33	208	100	6.013	7,6	2	185	269	394	On request	On request
1T458B	1.100	725	220-1.450	300	700	250	33	208	100	6.013	7,6	2	185	291	407	On request	On request
1,5T458B	1.550	675	200-1.350	300	700	250	33	208	100	6.013	7,6	2	185	272	399	On request	On request
1,5T458B	1.500	725	220-1.450	300	700	250	33	208	100	6.013	7,6	2	185	285	412	On request	On request
2T458B	**2.400**	**675**	**200-1.350**	**340**	**850**	**250**	**33**	**270**	**170**	**7.700**	**9,7**	**2**	**207**	**274**	**532**	**On request**	**On request**
2T458B	2.200	725	220-1.450	340	850	250	33	270	170	7.700	9,7	2	207	286	544	On request	On request
2T458B	**2.000**	**800**	**220-1.600**	**340**	**850**	**250**	**33**	**270**	**170**	**7.700**	**9,7**	**2**	**207**	**305**	**578**	**On request**	**On request**
2T458B	1.700	915	350-1.830	340	850	250	33	270	170	7.700	9,7	2	207	345	625	On request	On request
2T458B	**2.400**	**675**	**200-1.350**	**340**	**850**	**250**	**33**	**270**	**170**	**7.700**	**9,7**	**3**	**207**	**274**	**532**	**On request**	**On request**
2T458B	2.200	725	220-1.450	340	850	250	33	270	170	7.700	9,7	3	207	286	544	On request	On request
2T458B	**2.000**	**800**	**220-1.600**	**340**	**850**	**250**	**33**	**270**	**170**	**7.700**	**9,7**	**3**	**207**	**305**	**578**	**On request**	**On request**
2T458B	1.700	915	350-1.830	340	850	250	33	270	170	7.700	9,7	3	207	345	625	On request	On request
3T458B	3.200	675	220-1.350	340	850	250	36	339	170	8.950	11,3	3	242	261	705	On request	On request
3T458B	3.000	725	250-1.450	340	850	250	36	339	170	8.950	11,3	3	242	275	723	On request	On request
3T458B	2.800	800	250-1.600	340	850	250	36	339	170	8.950	11,3	3	242	287	751	On request	On request
3T458B	2.500	915	300-1.830	340	850	250	36	339	170	8.950	11,3	3	242	303	780	On request	On request
3T458B	2.100	1100	800-2.200	340	850	250	36	339	170	8.950	11,3	3	242	355	870	On request	On request
4T458B	3.900	675	250-1.350	420	1.000	300	36	383	160	12.591	11,2	3	270	319	993	On request	On request
4T458B	3.700	725	250-1.450	420	1.000	300	36	383	160	12.591	11,2	3	270	323	1.026	On request	On request
4T458B	3.500	800	250-1.600	420	1.000	300	36	383	160	12.591	11,2	3	270	329	1.075	On request	On request
4T458B	3.400	915	350-1.830	420	1.000	300	36	383	160	12.591	11,2	3	255	356	1.121	On request	On request
4T458B	2.800	1100	800-2.200	420	1.000	300	36	383	160	12.591	11,2	3	255	405	1.184	On request	On request
4T458B	3.900	675	250-1.350	420	1.000	300	36	516	160	12.591	11,2	4	270	319	993	On request	On request

Model	Cap. kg	LCD mm	A1-A2 mm	F mm	G mm	K mm	L mm	M mm	N mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofGZ mm	Weight kg	Price 人民币	Add-on price f. c-pads w. coating 人民币
4T458B	3.700	725	250-1.450	420	1.000	300	36	516	160	12.591	11,2	4	270	323	1.026	On request	On request
4T458B	3.500	800	250-1.600	420	1.000	300	36	516	160	12.591	11,2	4	270	329	1.075	On request	On request
4T458B	3.400	915	350-1.830	420	1.000	300	36	516	160	12.591	11,2	4	255	356	1.121	On request	On request
4T458B	2.800	1100	800-2.200	420	1.000	300	36	516	160	12.591	11,2	4	255	405	1.184	On request	On request
5T458B	4.750	800	250-1.600	420	1.000	300	40	350	160	12.591	11,2	4	315	359	1.162	On request	On request
5T458B	4.200	915	350-1.830	420	1.000	300	40	350	160	12.591	11,2	4	315	389	1.213	On request	On request
5T458B	3.900	1000	500-2.000	420	1.000	300	40	350	160	12.591	11,2	4	303	414	1.242	On request	On request
5T458B	3.300	1200	650-2.400	420	1.000	300	40	350	160	12.591	11,2	4	325	462	1.374	On request	On request
6T458B	5.500	900	400-1.800	420	1.000	300	40	350	160	19.998	17,9	4	327	390	1.413	On request	On request
6T458B	4.600	1100	600-2.200	420	1.000	300	40	350	160	19.998	17,9	4	327	422	1.529	On request	On request

Contact pads: 1T-3T with polyurethane coating, 4T and above with rubber coating
Capacity related to max. roll diameter.
The short arm is hydraulically adjustable in 45° position.
Optional: restricted to 180° rotation, continuous contact pads.
For taking up horizontal rolls, 5-degree mast forward tilt is required.
For contact pad coatings see accessories in the pricelist.
Attachment with sideshift Model T498B (add-on price).

Rotating Roll Clamp T458B