

- short arm fixed - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A1- A2 mm	F mm	G mm	K mm	L mm	M mm	N mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币	Add-on price f. c- pads w. coating 人民币
1T458BC-2	1.200	675	450-1.350	300	700	250	33	208	100	6.013	7,6	2	185	279	397	On request	On request
2T458BC-2	2.400	675	450-1.350	340	850	250	33	270	170	7.700	9,7	2	207	278	556	On request	On request
2T458BC-2	2.000	800	650-1.600	340	850	250	33	270	170	7.700	9,7	2	207	311	606	On request	On request
2T458BC-2	2.400	675	450-1.350	340	850	250	33	270	170	7.700	9,7	3	207	278	556	On request	On request
2T458BC-2	2.000	800	650-1.600	340	850	250	33	270	170	7.700	9,7	3	207	311	606	On request	On request
3T458BC-2	3.200	675	450-1.350	340	850	250	36	339	170	8.950	11,3	3	242	282	677	On request	On request
3T458BC-2	2.800	800	650-1.600	340	850	250	36	339	170	8.950	11,3	3	242	317	738	On request	On request
4T458BC-2	3.700	725	550-1.450	420	1.000	300	36	383	160	12.591	11,2	3	270	344	1.033	On request	On request
4T458BC-2	3.500	800	600-1.600	420	1.000	300	36	383	160	12.591	11,2	3	270	350	1.084	On request	On request
4T458BC-2	3.700	725	550-1.450	420	1.000	300	36	351	160	12.591	11,2	4	270	344	1.033	On request	On request
4T458BC-2	3.500	800	600-1.600	420	1.000	300	36	351	160	12.591	11,2	4	270	350	1.084	On request	On request
5T458BC-2	4.750	800	600-1.600	420	1.000	300	40	350	160	12.591	11,2	4	315	367	1.163	On request	On request
5T458BC-2	4.200	915	700-1.830	420	1.000	300	40	350	160	12.591	11,2	4	315	397	1.214	On request	On request
6T458BC-2	5.500	900	700-1.800	420	1.000	300	40	350	160	19.998	17,9	4	327	395	1.419	On request	On request
6T458BC-2	4.600	1100	900-2.200	420	1.000	300	40	350	160	19.998	17,9	4	327	432	1.544	On request	On request

Contact pads: 1T-3T with polyurethane coating, 4T and above with rubber coating

Capacity related to max. roll diameter.

For taking up horizontal rolls, 5-degree mast forward tilt is required.

Optional: restricted to 180° rotation, Tissue version, short arm with continuous contact pads.

For contact pad coatings see accessories in the pricelist.

Attachment with sideshift Model T498BC-2 (add-on price).



Rotating Roll Clamp T458BC-2
