

- short arm fixed - 2 hydraulic functions

## Technical Data

Model	Cap. kg	LCD mm	A1- A2 mm	F mm	G mm	K mm	L mm	M mm	N mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币	Add-on price f. c- pads w. coating 人民币
<b>1T458BC</b>	1.200	675	450- 1.350	300	700	250	33	208	100	6.013	7,6	2	185	279	397	On request	On request
<b>2T458BC</b>	2.400	675	450- 1.350	340	850	250	33	270	170	7.700	9,7	2	207	278	556	On request	On request
<b>2T458BC</b>	2.000	800	650- 1.600	340	850	250	33	270	170	7.700	9,7	2	207	310	606	On request	On request
<b>2T458BC</b>	2.400	675	450- 1.350	340	850	250	33	270	170	7.700	9,7	3	207	278	556	On request	On request
<b>2T458BC</b>	2.000	800	650- 1.600	340	850	250	33	270	170	7.700	9,7	3	207	310	606	On request	On request
<b>3T458BC</b>	3.200	675	450- 1.350	340	850	250	36	339	170	8.950	11,3	3	242	282	677	On request	On request
<b>3T458BC</b>	2.800	800	650- 1.600	340	850	250	36	339	170	8.950	11,3	3	242	317	738	On request	On request
<b>4T458BC</b>	3.700	725	550- 1.450	420	1.000	300	36	383	160	12.591	11,2	3	270	344	1.033	On request	On request
<b>4T458BC</b>	3.500	800	600- 1.600	420	1.000	300	36	383	160	12.951	11,2	3	270	350	1.083	On request	On request
<b>4T458BC</b>	3.700	725	550- 1.450	420	1.000	300	36	516	160	12.591	11,2	4	270	344	1.033	On request	On request
<b>4T458BC</b>	3.500	800	600- 1.600	420	1.000	300	36	516	160	12.591	11,2	4	270	350	1.083	On request	On request
<b>5T458BC</b>	4.750	800	600- 1.600	420	1.000	300	40	350	350	12.591	11,2	4	315	367	1.163	On request	On request
<b>5T458BC</b>	4.200	915	700- 1.830	420	1.000	300	40	350	350	12.591	11,2	4	315	397	1.214	On request	On request
<b>6T458BC</b>	5.500	900	700- 1.800	420	1.000	300	40	350	350	19.998	17,9	4	327	395	1.419	On request	On request
<b>6T458BC</b>	4.600	1100	900- 2.200	420	1.000	300	40	350	350	19.998	17,9	4	327	432	1.544	On request	On request

Contact pads: 1T-3T with polyurethane coating, 4T and above with rubber coating

Capacity related to max. roll diameter.

For taking up horizontal rolls, 5-degree mast forward tilt is required.

Optional: restricted to 180° rotation, continuous contact pads.

For contact pad coatings see accessories in the pricelist.

Attachment with sideshift Model T498BC (add-on price).



## Rotating Roll Clamp T458BC

---

---

---