

- short arm adjustable in 45° position (BCR = fixed) - continuous contact pads - 2 hydraulic function

Technical Data

Model	Cap. kg	LCD mm	A1-A2 mm	G mm	K mm	L mm	M mm	Md Δ -P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
1T458BCR	1.200	675	450- 1.350	1.200	250	33	208	6.013	7,6	2	185	318	423	On request
1T458BCR	1.100	725	500- 1.450	1.200	250	33	208	6.013	7,6	2	185	322	439	On request
1,5T458BR	1.150	675	200- 1.350	2.000	250	33	208	6.013	7,6	2	185	369	476	On request
1,5T458BR	800	800	250- 1.600	2.000	250	33	208	6.013	7,6	2	185	410	517	On request
2T458BR	2.400	675	200- 1.350	2.000	250	33	270	7.700	9,7	2	207	360	647	On request
2T458BR	2.000	800	220- 1.600	2.000	250	32	270	7.700	9,7	2	207	399	697	On request
2T458BR	1.700	915	350- 1.830	2.000	250	32	270	7.700	9,7	2	207	442	743	On request
2T458BR	2.400	675	200- 1.350	2.000	250	33	270	7.700	9,7	3	207	360	647	On request
2T458BR	2.000	800	220- 1.600	2.000	250	32	270	7.700	9,7	3	207	399	697	On request
2T458BR	1.700	915	350- 1.830	2.000	250	32	270	7.700	9,7	3	207	442	743	On request

BCR Version with fixed short arm.

Capacity related to max. roll diameter.

The short arm is hydraulically adjustable in 45° position.

All models available restricted to 180°.

For taking up horizontal rolls, 5-degree mast forward tilt is required.

For contact pad coatings see accessories in the pricelist.

Attachment with sideshift Model T498BR/T498BCR (add-on price).



Rotating Tyre Clamp T458BR
