

- short arm adjustable in 45° position (BCT = fixed) - split contact pads - 2 hydraulic functions

Technical Data

| Model | Cap. kg | LCD mm | A1- A2 mm | G mm | K mm | L mm | M mm | Md Δ-P = 125 bar Nm | Req. oil volume per rotation ltr. | ISO | V mm | CofG Z mm | Weight kg | Price 人民币 | Add-on price f. c- pads w. rubber coating 人民币 |
|-----------------|------------|-----------|-----------------|---------|---------|---------|---------|-------------------------------|---|-----|---------|-----------------|--------------|---------------|--|
| 1T458BCT | 1.200 | 675 | 450- 1.350 | 850 | 300 | 33 | 208 | 6.013 | 7,6 | 2 | 185 | 293 | 407 | On request | On request |
| 1T458BCT | 1.100 | 725 | 500- 1.450 | 850 | 300 | 33 | 208 | 6.013 | 7,6 | 2 | 185 | 296 | 423 | On request | On request |
| 2T458BCT | 2.000 | 800 | 650- 1.600 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 2 | 207 | 385 | 679 | On request | On request |
| 2T458BT | 2.000 | 800 | 220- 1.600 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 2 | 207 | 388 | 685 | On request | On request |
| 2T458BT | 1.700 | 915 | 350- 1.830 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 2 | 207 | 431 | 731 | On request | On request |
| 2T458BCT | 2.000 | 800 | 650- 1.600 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 3 | 207 | 385 | 679 | On request | On request |
| 2T458BT | 2.000 | 800 | 220- 1.600 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 3 | 207 | 388 | 685 | On request | On request |
| 2T458BT | 1.700 | 915 | 350- 1.830 | 1.400 | 300 | 33 | 270 | 7.700 | 9,7 | 3 | 207 | 431 | 731 | On request | On request |
| 3T458BT | 2.500 | 915 | 300- 1.830 | 1.400 | 300 | 36 | 338 | 8.950 | 11,3 | 3 | 242 | 426 | 876 | On request | On request |
| 3T458BT | 2.100 | 1100 | 800- 2200 | 1.400 | 300 | 36 | 338 | 8.950 | 11,3 | 3 | 242 | 485 | 968 | On request | On request |
| 4T458BT | 3.400 | 915 | 350- 1.830 | 1.800 | 350 | 36 | 383 | 12.591 | 11,2 | 3 | 255 | 470 | 1.286 | On request | On request |
| 4T458BT | 2.800 | 1100 | 800- 2.200 | 1.800 | 350 | 36 | 383 | 12.591 | 11,2 | 3 | 255 | 533 | 1.350 | On request | On request |
| 4T458BT | 3.400 | 915 | 350- 1.830 | 1.800 | 350 | 36 | 516 | 12.591 | 11,2 | 4 | 255 | 470 | 1.286 | On request | On request |
| 4T458BT | 2.800 | 1100 | 800- 2.200 | 1.800 | 350 | 36 | 516 | 12.591 | 11,2 | 4 | 255 | 533 | 1.350 | On request | On request |
| 5T458BT | 3.700 | 1000 | 500- 2000 | 1.800 | 350 | 40 | 350 | 12.591 | 11,2 | 4 | 315 | 536 | 1.402 | On request | On request |
| 5T458BT | 3.100 | 1200 | 650- 2.400 | 1.800 | 350 | 40 | 350 | 12.591 | 11,2 | 4 | 315 | 565 | 1.491 | On request | On request |

BCT Version with BCT Version with fixed short arm.

Capacity related to max. roll diameter.

The short arm is hydraulically adjustable in 45° position.

All models available restricted to 180°.

For taking up horizontal rolls, 5-degree mast forward tilt is required.

Recommended length of contact pads: 70 % of roll width.
For contact pad coatings see accessories in the pricelist.
Attachment with sideshift Model T498BT/T498BCT (add-on price).



Rotating Tissue Roll Clamp T458BT
