Rotating Tissue Roll Clamp T458BT (23.11.2026)

360° rotation continuous

- short arm adjustable in 45° position (BCT = fixed) - split contact pads - 2 hydraulic functions

Model	Cap. kg	LCD mm	A1-A2 mm	G mm	K mm	L mm	M mm	Md Δ-P = 125 bar Nm	Req. oil volume per rotation ltr.	ISO	V mm	CofG Z mm	Weight kg	Price 人民币	Add-on price f. c-pads w. rubber coating 人民币
1T458BCT	1.200	675	450-1.350	850	300	33	208	6.013	7,6	2	185	293	407	On request	On request
1T458BCT	1.100	725	500-1.450	850	300	33	208	6.013	7,6	2	185	296	423	On request	On request
2T458BCT	2.000	800	650-1.600	1.400	300	33	270	7.700	9,7	2	207	385	679	On request	On request
2T458BT	2.000	800	220-1.600	1.400	300	33	270	7.700	9,7	2	207	388	685	On request	On request
2T458BT	1.700	915	350-1.830	1.400	300	33	270	7.700	9,7	2	207	431	731	On request	On request
2T458BCT	2.000	800	650-1.600	1.400	300	33	270	7.700	9,7	3	207	385	679	On request	On request
2T458BT	2.000	800	220-1.600	1.400	300	33	270	7.700	9,7	3	207	388	685	On request	On request
2T458BT	1.700	915	350-1.830	1.400	300	33	270	7.700	9,7	3	207	431	731	On request	On request
3T458BT	2.500	915	300-1.830	1.400	300	36	338	8.950	11,3	3	242	426	876	On request	On request
3T458BT	2.100	1100	800-2200	1.400	300	36	338	8.950	11,3	3	242	485	968	On request	On request
4T458BT	3.400	915	350-1.830	1.800	350	36	383	12.591	11,2	3	255	470	1.286	On request	On request
4T458BT	2.800	1100	800-2.200	1.800	350	36	383	12.591	11,2	3	255	533	1.350	On request	On request
4T458BT	3.400	915	350-1.830	1.800	350	36	516	12.591	11,2	4	255	470	1.286	On request	On request
4T458BT	2.800	1100	800-2.200	1.800	350	36	516	12.591	11,2	4	255	533	1.350	On request	On request
5T458BT	3.700	1000	500-2000	1.800	350	40	350	12.591	11,2	4	315	536	1.402	On request	On request
5T458BT	3.100	1200	650-2.400	1.800	350	40	350	12.591	11,2	4	315	565	1.491	On request	On request

BCT Version witBCT Version with fixed short arm.
Capacity related to max. roll diameter.
The short arm is hydraulically adjustable in 45° position.
All models available restricted to 180°.
For taking up horizontal rolls, 5-degree mast forward tilt is required.
Recommended lenght of contact pads: 70 % of roll width.
For contact pad coatings see accessories in the pricelist.
Attachment with sideshift Model T498BT/T498BCT (add-on price).

Rotating Tissue Roll Clamp T458BT