



with independent sideshift - without forks - for forks acc. to ISO 2330 - 2 hydraulic functions

## Technical Data

Model	Cap. kg	LCD mm	A mm	A1 mm	A2 mm	B mm	C mm	S mm	suitable for max. fork width mm	ISO	V mm	CofG Z mm	CofG <sub>v</sub> Y mm	Weight kg	Price 人民币
<b>2T466BI</b>	2.500	500	150-850	250-950	320-1.020	1.040	240	±100	120	2	133	58	218	156	On request
<b>2T466BI</b>	2.500	500	150-950	250-1.050	320-1.120	1.150	240	±100	120	2	133	58	217	163	On request
<b>2,5T466BI</b>	2.500	600	150-850	250-950	320-1.020	1.040	240	±100	120	2	133	60	218	158	On request
<b>2,5T466BI</b>	2.500	600	150-950	250-1.050	320-1.120	1.150	240	±100	120	2	133	60	217	165	On request
<b>3,5T466BI</b>	3.500	500	180-980	250-1.050	320-1.120	1.150	240	±100	130	3	138	61	267	173	On request
<b>3,5T466BI</b>	3.500	500	180-1.180	250-1.250	320-1.320	1.350	240	±100	130	3	138	59	265	197	On request
<b>4,8T466BI<sup>1)</sup></b>	5.000	600	180-1.180	250-1.250	320-1.320	1.350	255	±100	150	3	148	65	268	279	On request
<b>4,8T466BI<sup>1)</sup></b>	5.000	600	180-1.360	250-1.430	320-1.500	1.550	255	±100	150	3	148	62	266	319	On request
<b>6T466BI</b>	6.000	600	260-1.170	350-1.260	440-1.350	1.460	330	±100	150	4	171	68	343	402	On request
<b>6T466BI</b>	6.000	600	260-1.360	350-1.450	440-1.540	1.650	330	±160	150	4	171	68	345	435	On request
<b>6T466BI</b>	6.000	600	260-1.560	350-1.650	440-1.740	1.860	330	±160	150	4	171	68	343	468	On request
<b>8T466BI</b>	8.000	600	260-1.560	350-1.650	440-1.740	1.860	330	±160	150	4	171	68	343	468	On request
<b>8T466BI</b>	8.000	600	260-1.760	350-1.850	440-1.940	2.060	330	±160	150	4	171	65	341	523	On request
<b>8T466BI</b>	8.000	600	260-1.960	350-2.050	440-2.140	2.260	330	±160	150	4	171	65	340	559	On request

Model	Cap. kg	LCD mm	A mm	A1 mm	A2 mm	B mm	C mm	S mm	suitable for max. fork width mm	ISO	V mm	CofG Z mm	CofG Y mm	Weight kg	Price 人民币
<b>8T466BI</b>	8.000	600	260- 2.060	350- 2.150	440- 2.240	2.400	330	±160	150	4	171	64	340	586	On request

<b>10T466BI</b>	8.000	1.100	260- 1.760	360- 1.860	460- 1.960	2.060	370	±160	200	4	244	104	323	909	On request
<b>10T466BI</b>	8.000	1.100	260- 1.960	360- 2.060	460- 2.160	2.260	370	±160	200	4	244	102	322	979	On request
<b>10T466BI</b>	8.000	1.100	260- 2.060	360- 2.160	460- 2.260	2.400	370	±160	200	4	244	102	322	1.014	On request

1) 4,8T with capacity (kg/mm) 2.700/1.200 available upon request.

CofG and weight measurements do not take the cheek plates into account.

Load backrest see model T479 and T479.1

Forks see model T180.

Forks manually adjustable.

Fork carriage drawings, roller studs and chain anchors to be supplied by customer if necessary.

Not suitable for clamping between the forks.



### Specification:

The KAUP integrated Fork Positioner

T466BI has been specially designed with optimised visibility and residual capacity. Compared to hook-on Fork Positioners in the T466 range with even better, higher residual capacities this attachment is manufactured from well proven components and is suitable for moderately heavy duty tasks. The qualities of the range of T466BI Fork Positioners are particularly effective when different sizes of loads are regularly transported or different kinds of transportation are used - for example in logistics.

### Qualities:

- For moderately heavy operation - complete program with capacities of up to 10 tons
- Very good residual capacity
- Excellent visibility
- Supplied with welded forks
- Supplied optionally with screw on forks for wear intensive operation (A-version)
- Independent sideshift serially