Fork Positioner with Telescopic Forks T466B/T180CT (24.11.2026)

with independent sideshift - 2 hydraulic functions + solenoid valve

Model	Cap. retracted kg	LCD retr. mm	Cap. extended kg	LCD ext. mm	A mm	A1 mm	A2 mm	B mm	E mm	D mm	D1 mm	G1 mm	G2 mm	S mm	ISO	V mm	CofG Z mm	CofG Z1 mm	CofG$_v$ Y mm	Weight kg	Price 人民币
2T466B/2,5T180CT	2.020	600	850	1.450	180-880	250-950	320-1.020	1.040	163	56	45	1.200	2.050	100	2	138	341	445	145	340	On request
2T466B/2,5T180CT	2.020	600	850	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.200	2.050	100	2	138	336	438	146	346	On request
2T466B/2,5T180CT	2.020	600	850	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.200	2.050	100	2	138	328	427	148	357	On request
2T466B/2,5T180CT.1	2.020	600	850	1.450	180-880	250-950	320-1.020	1.040	163	56	45	1.350	2.350	100	2	138	390	520	137	356	On request
2T466B/2,5T180CT.1	2.020	600	850	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.350	2.350	100	2	138	385	512	138	362	On request
2T466B/2,5T180CT.1	2.020	600	850	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.350	2.350	100	2	138	375	499	140	373	On request
4,8T466B/3,5T180CT	3.500	600	1.600	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.200	2.050	100	3	153	294	381	185	454	On request
4,8T466B/3,5T180CT	3.500	600	1.600	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.200	2.050	100	3	153	285	369	188	473	On request
4,8T466B/3,5T180CT	3.500	600	1.600	1.450	180-1.360	250-1.430	320-1.500	1.550	163	56	45	1.200	2.050	100	3	153	277	354	191	493	On request
4,8T466B/3,5T180CT.1	3.500	600	1.600	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.350	2.350	100	3	153	335	445	178	471	On request
4,8T466B/3,5T180CT.1	3.500	600	1.600	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.350	2.350	100	3	153	325	431	181	490	On request
4,8T466B/3,5T180CT.1	3.500	600	1.600	1.450	180-1.360	250-1.430	320-1.500	1.550	163	56	45	1.350	2.350	100	3	153	315	417	184	510	On request
4,8T466B/4,5T180CT	4.500	600	1.850	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.200	2.050	100	3	153	294	381	185	454	On request
4,8T466B/4,5T180CT	4.500	600	1.850	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.200	2.050	100	3	153	285	369	188	473	On request
4,8T466B/4,5T180CT	4.500	600	1.850	1.450	180-1.360	250-1.430	320-1.500	1.550	163	56	45	1.200	2.050	100	3	153	277	354	191	493	On request
4,8T466B/4,5T180CT.1	4.500	600	1.850	1.450	180-980	250-1.050	320-1.120	1.150	163	56	45	1.350	2.350	100	3	153	335	445	178	471	On request
4,8T466B/4,5T180CT.1	4.500	600	1.850	1.450	180-1.180	250-1.250	320-1.320	1.350	163	56	45	1.350	2.350	100	3	153	325	431	181	490	On request
4,8T466B/4,5T180CT.1	4.500	600	1.850	1.450	180-1.360	250-1.430	320-1.500	1.550	163	56	45	1.350	2.350	100	3	153	315	417	184	510	On request
4,8T466B/4,8T180CT	5.000	600	2.070	1.450	180-980	250-1.050	320-1.120	1.150	163	61	50	1.200	2.050	100	3	153	307	392	181	475	On request
4,8T466B/4,8T180CT	5.000	600	2.070	1.450	180-1.180	250-1.250	320-1.320	1.350	163	61	50	1.200	2.050	100	3	153	299	380	184	494	On request
4,8T466B/4,8T180CT	5.000	600	2.070	1.450	180-1.360	250-1.430	320-1.500	1.550	163	61	50	1.200	2.050	100	3	153	290	368	187	514	On request
4,8T466B/4,8T180CT.1	5.000	600	2.070	1.450	180-980	250-1.050	320-1.120	1.150	163	61	50	1.350	2.350	100	3	153	350	457	173	494	On request
4,8T466B/4,8T180CT.1	5.000	600	2.070	1.450	180-1.180	250-1.250	320-1.320	1.350	163	61	50	1.350	2.350	100	3	153	340	443	176	513	On request
4,8T466B/4,8T180CT.1	5.000	600	2.070	1.450	180-1.360	250-1.430	320-1.500	1.550	163	61	50	1.350	2.350	100	3	153	330	429	179	533	On request

Incl. solenoid valve and accessory kit
All models with parallel movement
Load Backrest see model T479.1
Telescopic forks with hardox wear bar see telescopic forks accessories.
Load stop see accessories for telescopic forks.
For triplex mast an electric spring cable drum is necessary. See accessories in the pricelist.

Fork Positioner with Telescopic Forks T466B/T180CT